

VERSACHEM INC  
6643 42ND TERRACE N  
W PALM BEACH, FL 33407  
RON COSTELLO

BEC

BRAVO

P/N 27309

61309

61310

65010

65309

76000

73009

VersaChem Corporation 7-3C, 7-10, 270-10, 273-3C,  
MATERIAL SAFETY DATA SHEET 280-10, 613-3C, 613-3, 613-8,  
MATL NAME: Silicone Sealant; - Part #8 613-10, 613-12, 650-3C, 650-10  
Emergency Telephone: (407) 845-2425

-----  
SECTION I - GENERAL INFORMATION  
-----

PROPER SHIPPING NAME(49CFR 172.101): NONE  
D.O.T. HAZARD NAME(49CFR 172.101): NONE  
D.O.T. ID NO(49CFR 172.101): NONE  
D.O.T. HAZARD CLASS(49CFR 172.101): NONE  
RCRA HAZARD CLASS(40CFR 261)(IF DISCARDED): NONE  
E.P.A. PRIORITY POLLUTANTS(40CFR 122.53): NONE  
NFPA = NATIONAL FIRE PROTECTION ASSOCIATION - 704  
HEALTH (NFPA): 1 FLAMMABILITY (NFPA): 1 REACTIVITY (NFPA): 0  
CAS NO: MIXTURE  
GENERIC DESCRIPTION: SILICONE

-----  
SECTION II - HAZARDOUS INGREDIENTS AS DEFINED IN 29 CFR 1910.1200  
(CARCINOGENS IDENTIFIED WITH AN ASTERISK \*)  
-----

CAS NO.	INGREDIENT	WT. %	EXPOSURE LIMITS
004253343	METHYLTRIAACETOXSILANE	2	SEE COMMENT BELOW.
017689779	ETHYLTRIAACETOXSILANE	3	SEE COMMENT BELOW.
007631869	SILICA	10	OSHA PEL: TWA 20 MPPCF ACGIH TLV: TWA 10 MG/M3 TOTAL DUST

COMMENT: OBSERVE LIMITS FOR ACETIC ACID, FORMED DURING CURING ON EXPOSURE TO WATER OR HUMID AIR. OSHA PEL: TWA 10 PPM. ACGIH TLV: TWA 10 PPM, STEL 15 PPM.

MATERIAL SAFETY DATA SHEET

MATL NAME: Silicone Sealant

SECTION III - EFFECTS OF OVEREXPOSURE

EYE: DIRECT CONTACT IRRITATES SLIGHTLY TO MODERATELY WITH REDNESS AND SWELLING.

SKIN: A SINGLE SHORT EXPOSURE (LESS THAN 24 HOURS) MAY IRRITATE. REPEATED PROLONGED CONTACT (24 TO 48 HOURS) MAY IRRITATE MODERATELY.

INHALATION: VAPOR OVEREXPOSURE MAY IRRITATE EYES, NOSE AND THROAT.

ORAL: SMALL AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS DURING USE, ETC., SHOULD NOT INJURE. SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.

COMMENTS: NO INJURY FROM SILICA DUST SHOULD OCCUR DURING REASONABLE USE. IF USE CREATES RESPIRABLE PARTICLES, SOME RESPIRATORY SYSTEM INJURY MAY OCCUR. CURED SEALANT IS NONHAZARDOUS.

THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. WE DO NOT KNOW OF ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: WIPE OFF AND FLUSH WITH WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS.

INHALATION: REMOVE TO FRESH AIR.

ORAL: NO FIRST AID SHOULD BE NEEDED.

COMMENT: NONE

SECTION V - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): OPEN CUP ABOVE 250F/120C

AUTOIGNITION: NOT DETERMINED

FLAMMABILITY LIMITS IN AIR : LOWER:N.D. UPPER: N.D.

EXTINGUISHING MEDIA: WATER WATER FOG X CO2 X DRY CHEMICAL X FOAM X OTHER

SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN

COMMENTS: N.D. - NOT DETERMINED.

SECTION VI - PHYSICAL DATA

BOILING POINT(@ 760 MM HG): NOT APPLICABLE

SPECIFIC GRAVITY (AT 77 DEG F/25 DEG C): 1.04

MELTING POINT: NOT APPLICABLE

VAPOR PRESSURE (AT 77 DEG F/25 DEG C): LESS THAN 5 MM

VAPOR DENSITY (AIR = 1 AT 77 DEG F/25 DEG C): ABOVE 1

PERCENT VOLATILE BY WEIGHT (%): LESS THAN 5

EVAPORATION RATE (ETHER = 1): NOT APPLICABLE

SOLUBILITY IN WATER(%): LESS THAN 0.1

ODOR, APPEARANCE, COLOR: ACETIC ACID-LIKE, PASTE. Color based on part no.

NOTE: THE ABOVE INFORMATION IS NOT INTENDED FOR USE IN PREPARING PRODUCT SPECIFICATIONS.

MATERIAL SAFETY DATA SHEET

MATL NAME: Silicone Sealant

-----  
SECTION VII - REACTIVITY DATA  
-----

STABILITY: STABLE

INCOMPATIBILITY(MATERIAL TO AVOID): OXIDIZING MATERIAL CAN CAUSE A REACTION.  
AIR OR MOISTURE CAUSES CURING AND ACETIC ACID VAPORS FORM.

CONDITIONS TO AVOID: EXPOSURE TO AIR OR MOISTURE UNTIL READY TO USE.

HAZARDOUS DECOMPOSITION PRODUCTS: SILICON DIOXIDE, CARBON DIOXIDE, AND TRACES  
OF INCOMPLETELY BURNED CARBON PRODUCTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NOT APPLICABLE

COMMENTS: NONE

-----  
SECTION VIII - SPILL, LEAK, MAINTENANCE/REPAIR AND DISPOSAL PROCEDURES  
-----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE PRODUCT AND  
CONTAIN FOR SALVAGE OR DISPOSAL.

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE. REMOVE CONTAMINATED  
CLOTHING AND SHOES AS SOON AS PRACTICAL AND CLEAN THOROUGHLY BEFORE REUSE.  
RUBBER OR PLASTIC GLOVES ARE RECOMMENDED.

INHALATION: USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS  
ADEQUATE OR AIR SAMPLING DATA SHOW EXPOSURES ARE WITHIN TLV AND PEL GUIDE-  
LINES.

WASTE DISPOSAL METHOD: DOW CORNING SUGGESTS THAT ALL LOCAL, STATE AND FEDERAL  
REGULATIONS CONCERNING HEALTH AND POLLUTION BE REVIEWED TO DETERMINE APPROVED  
DISPOSAL PROCEDURES. CONTACT DOW CORNING IF THERE ARE ANY DISPOSAL QUESTIONS.

D.O.T. (49CFR 171.8)/E.P.A. (40CFR 117) SPILL REPORTING INFORMATION  
HAZARDOUS SUBSTANCE: NONE REPORTABLE QUANTITY: NOT APPLICABLE  
CONCENTRATION OF HAZARDOUS SUBSTANCE: NOT APPLICABLE  
REPORTABLE QUANTITY OF PRODUCT: NOT APPLICABLE

COMMENTS: NONE

-----  
SECTION IX - ROUTINE HANDLING PRECAUTIONS  
-----

PROTECTIVE EQUIPMENT:

EYES: USE PROPER EYE PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN \*: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE. REMOVE CONTAMINATED  
CLOTHING AND SHOES AS SOON AS PRACTICAL AND THOROUGHLY CLEAN BEFORE REUSE.  
RUBBER OR PLASTIC GLOVES ARE RECOMMENDED.

INHALATION: USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS  
ADEQUATE OR AIR SAMPLING DATA SHOW EXPOSURES ARE WITHIN TLV AND PEL GUIDE-  
LINES.

VENTILATION:

LOCAL EXHAUST: MAY BE NEEDED.  
MECHANICAL (GENERAL): RECOMMENDED

SUITABLE RESPIRATOR: ACID GAS/ORGANIC VAPOR TYPE.

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING, USE AT ELEVATED  
TEMPERATURES, OR AEROSOL/SPRAY APPLICATIONS, MAY REQUIRE ADDED PRECAUTIONS.  
\* GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED  
FROM THE SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.  
COMMENTS: AVOID BREATHING VAPORS AND EYE AND SKIN CONTACT. USE ONLY WITH  
ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY.

MATERIAL SAFETY DATA SHEET

MATL NAME: Silicone Sealant

-----  
SECTION X - SPECIAL PRECAUTIONS  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE BELOW 90F/32C. KEEP CONTAINER CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONS: TRACES OF FORMALDEHYDE AND OTHER THERMAL DECOMPOSITION PRODUCTS MAY FORM AT TEMPERATURES ABOVE 150C IN THE PRESENCE OF AIR. PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURE WITHIN INHALATION GUIDELINES WHEN HANDLING AT ELEVATED TEMPERATURES.

COMMENTS: NONE

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

Prepared By:



Ronald J. Costello

\_\_\_\_\_  
*President*