

MSDS Form #1, Generic Waterborne Latex Coatings

The following Material Safety Data Sheet (MSDS) is being provided pursuant to requirements of the Fed/OSHA (29 CFR 1910.1200) and Cal/OSHA (8 CCR 5194) Hazard Communication Standards. The health and hazards information given here is based on data believed to be accurate by Dunn-Edwards Corporation; we do not, however, assume any liability for the accuracy or completeness of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones that may exist. All persons intending to rely on any recommendation, or to use any technique, equipment, or material mentioned should first satisfy themselves that they can meet all applicable safety and health standards.

The following MSDS supersedes any previously issued MSDS for each product covered. The reader is advised to destroy any obsolete MSDS and refer only to this MSDS. As permitted by OSHA, each MSDS may apply to a class of products, which have similar hazards and contents. Products covered by this MSDS are listed below:

W 101-Series: VINYLASTIC	W 709: EFF-STOP
W 101V: VINYLASTIC	W 713: M-P PRIME
W 102: PROSEAL	W 715: ULTRA-GRIP
W 203: ENDURA-COAT	W 801-Series: VIN-L-STRIPE
W 203V: ENDURA-COAT	W 810-Series: TUFF-FLOOR
W 304: BLOCFIL Medium	W 810-Series: TUFF-FLOOR
W 305: BLOCFIL Smooth	W 901-Series: PERMASHEEN
W 315: Concrete Block Filler	W 901V-Series: PERMASHEEN CA Formula
W 320: FLEX-TEX Fine	W 940-Series: PERMASHELL
W 321: FLEX-TEX Smooth	W 940V-Series: PERMASHELL CA Formula
W 322: FLEX-TEX Medium	W 960-Series: PERMAGLOSS
W 323: FLEX-TEX Coarse	W 960E-Series: PERMAGLOSS CA Formula
W 401-Series: DECOVEL	W 2091: Vinyl Stipple Flat
W 410-Series: COVER-KOTE II	W 2140-Series: QUIK-WALL III
W 411-Series: SUPREMA	W 2397: New Drywall Latex Wall Sealer
W 411E-Series: SUPREMA	W 2400: Latex Enamel Undercoater
W 420-Series: WALLTONE	W 2456: STAY-KOOL
W 430-Series: ACRY-BOND	W 3447-Series: DURAWALL
W 440-Series: DECOSHEEN	W 3954: Low Sheen Latex Enamel
W 440V-Series: DECOSHEEN	W 4503-Series: Int/Ext Latex S/G Enamel
W 450-Series: DECOGLO	W 4601-Series: S/G Int. Latex Enamel
W 450V-Series: DECOGLO	W 5537: Eggshell Latex Enamel
W 701-Series: EVERSIELD	W 5807: Nevada Exterior Latex Flat
W 704-Series: ACRI-FLAT	W 5824: Elastomeric Roof Coating
W 704V-Series: ACRI-FLAT	W 5827: High Hide PVA Sealer
W 705-Series: ENDURACRYL	W 5852: Production Gloss Latex Enamel
W 707: UNIKOTE	W 5917: Latex Low Sheen
W 707V: UNIKOTE	W 5946: Int/Ext Latex Low Sheen
W 708: E-Z PRIME	W 5950-Series: Interior Latex Flat

7/13/07 (10/3/06)

MSDS Form #1, Generic Waterborne Latex Coatings - continued

W 5995: Graffiti Cover-Up, Tan
W 5996: Graffiti Cover-Up, Gray
W 6026: TUFFWALL
W 6035: Wallboard Sealer Pigmented
W 6078: AQUAFALL Low Sheen
W 6079: AQUAFALL Flat
W 6139: Acrylic Elastomeric Coating
W 6160: VERSAGLO
W 6196: Interior Latex Flat
W 6198: Interior Washable Latex Flat
W 6220V: VERSAGLOSS
W 6230: VERSAWALL
W 6230V: VERSAWALL
W 6232: ACRI-LOC
W 6250: VERSASATIN
W 6266: Ready-to-Use Interior Latex Flat
W 6267: Ready-to-Use Nevada Ext Latex Flat
W 6270: AQUAFALL Eggshell
W 6300: TILT-PRIME
W 6305: TILT-KOTE
W 6315: FLEX-PRIME
W 6324: PREP-SEAL
W 6325: INTER-KOTE
W 6329: Concrete Block Filler
W 6400: ULTRA-SCRUB
W 6401: QUIK-WALL
W 6402: SUPER-WALL
W 6403: SUPER-WALL Ready-to-Use
W 7300: SPARTASHEEN
W 7400: SPARTASHELL
W 7500: SPARTAGLO
W 7600V: SPARTAGLOSS
Z 6019: Interior Latex Eggshell Stipple
Z 6268: Int/Ext Acrylic Flat
W 1101: PAR White Interior Latex Enamel

MATERIAL SAFETY DATA SHEET

DUNN-EDWARDS CORPORATION
4885 EAST 52ND PLACE
LOS ANGELES, CA 90040-2828

EMERGENCY TELEPHONE NUMBER:
(800) 733-3866, EXTENSION 2640

DATE OF PREPARATION: 07/01/03

INFORMATION TELEPHONE NUMBER:
(323) 771-3330, EXTENSION 2640

SECTION I - PRODUCT IDENTIFICATION

MSDS FORM #1
GENERIC WATERBORNE LATEX COATINGS
(SEE INDEX FOR PRODUCTS COVERED)

HMS CODES: H F R PP
1 0 0 E

U.S. DOT SHIPPING DESCRIPTION: (Non-Regulated)

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS NUMBER	%WT	ACGIH	OSHA EXPOSURE LIMITS				VAPOR PRESS mmHg @ TEMP
			TLV/TWA PPM	TWA	STEL	MG/M ³	PPM	
Propylene Glycol	00057-55-6	<5%	-	-	-	-	-	0.1 @ 68°F
Texanol Ester Alcohol	25265-77-4	<5%	-	-	-	-	-	0.1 @ 68°F

SECTION III - PHYSICAL AND CHEMICAL DATA

BOILING RANGE: 200-225°F
SPECIFIC GRAVITY (H₂O=1): 1.4
SOLUBILITY IN WATER: Partly soluble.
APPEARANCE AND ODOR: Liquid dispersion with mild odor.

EVAPORATION RATE: Slower Than Ether.
VAPOR DENSITY: Heavier Than Air.
VOLATILE VOLUME: 60%

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: N/A
FLASH POINT: N/A LEL: N/A UEL: N/A
EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO₂, Dry Chemical, Water Fog.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Liquid material is non-combustible, but dried films are capable of supporting combustion when in contact with open flames. Closed containers can develop internal pressure and may rupture when subjected to extreme heat.
SPECIAL FIREFIGHTING PROCEDURES: Use self-contained breathing apparatus in confined spaces. Observe recommended procedures for handling ordinary combustible materials.

SECTION V - HEALTH HAZARD DATA

POTENTIAL ROUTES OF ENTRY / SIGNS AND SYMPTOMS OF EXPOSURE

INHALATION: Exposure to high vapor concentration may irritate mucous membranes and respiratory tract. Extreme overexposure may produce dizziness, headache, and nausea.
EYE CONTACT: Direct contact may cause eye irritation, redness, and tearing.
SKIN CONTACT: Prolonged contact may cause transient reddening of the skin.
SKIN ABSORPTION: Available information provides no evidence of adverse effects.
INGESTION: May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Pre-existing eye, skin, and respiratory system disorders, and unusual allergic sensitivity.

CHRONIC OR DELAYED HEALTH HAZARDS: Available information provides no evidence of chronic or delayed health hazards associated with exposure to this product.

CARCINOGENICITY: NTP? NO. IARC MONOGRAPHS? NO. OSHA REGULATED? NO.

EMERGENCY AND FIRST AID PROCEDURES: If affected by inhalation of vapor, move victim to fresh air. If not breathing, apply artificial respiration and call emergency medical care. For eye contact, flush eyes with fresh water for at least 15 minutes. If irritation persists, seek medical attention. For

skin contact, wash thoroughly with soap and water. Remove any contaminated clothing. If swallowed, have victim drink enough fresh water to ensure dilution. Call emergency medical care.

SECTION VI - REACTIVITY DATA

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion can produce carbon monoxide and/or carbon dioxide.

CONDITIONS TO AVOID: Avoid storage or use at temperatures below 40°F. Avoid freezing.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid water-reactive materials, strong oxidizers, acids and alkalis.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING, STORAGE, AND DISPOSAL

PRECAUTIONS FOR HANDLING AND STORAGE: Keep containers closed when not in use. Do not handle or store near heat, flame, or strong oxidizers, acids and alkalis. Store in cool, well-ventilated area. Rotate stock, use older material first. Inspect all containers for leaks.

STEPS TO TAKE IF MATERIAL IS RELEASED OR SPILLED: Dike and absorb spilled liquid with inert material such as clay granules, sand, earth, or sawdust. Use rags to clean up small amounts of spilled material.

WASTE DISPOSAL METHOD: Collect contaminated absorbent material and rags into a suitable container and dispose in accordance with all applicable local, state, and federal regulations.

SECTION VIII - CONTROL MEASURES FOR SAFE USE

RESPIRATORY PROTECTION: For spray application, use particulate filter mask to avoid breathing spray mist. Exposed persons with unusual allergic sensitivity may need organic vapor respirator (NIOSH/MSHA TC 23C or equivalent).

VENTILATION: For interior use, general mechanical ventilation may be sufficient to disperse vapor. Otherwise, open doors and windows or use portable fans to provide local exhaust.

EYE PROTECTION: Use safety glasses, goggles, or face shield to protect eyes.

PROTECTIVE GLOVES: Use waterproof gloves (e.g., latex, vinyl, rubber, neoprene) to avoid skin contact.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Waterproof headcovering and general protective clothing are recommended for protection as necessary.

WORK/HYGIENIC PRACTICES: Wash hands and face before eating.

SECTION IX - SPECIAL CAUTIONS

Do not store in areas subject to freezing temperatures. Keep above 40°F at all times. Use only with adequate ventilation or protection. Avoid breathing spray mist or vapor. Do not ingest. Avoid contact with skin. Close container after each use. Keep out of reach of children.

***** DISCLAIMER *****

THE INFORMATION CONVEYED ABOVE, ALTHOUGH OBTAINED FROM SOURCES WE CONSIDER RELIABLE, IS FURNISHED BY DUNN-EDWARDS CORPORATION WITHOUT ANY WARRANTY (WHETHER EXPRESS OR IMPLIED) AS TO ITS ACCURACY, ADEQUACY, OR APPLICABILITY TO ANY PARTICULAR NEEDS OR CIRCUMSTANCES.